



GREASE 182 DS (190kg)

Grease, Lithium

MINERAL

U310000

3/25/2025

V 25,2

Lithium grease for cardans.

DESCRIPTION

GREASE182 DS is an excellent general purpose grease for the lubrication of moderately loaded parts:

- Joints
- Bearings
- (Crank-)shafts
- Cardans

ADVANTAGES

- Excellent adhesion.
- Very good lubricating effect.
- Enhanced lubricity and anti-wear ability.
- Very good retention of its properties under all working conditions.
- Easily applicable with various pressurized lubricators.
- Good anti-corrosion protection.

NORMS

/APPROVALS

Lithium

SPECIFICATIONS

-20°C - 140°C

RECOMMENDATIONS

Droppoint 190°C

AVAILABILITY

	Bulk	IBC	Barrel	60L/53kg	20L steel	20L/ 18 kg plastic	4X5L	12X1L Specials	small / 400 gr
U310000			U310000	U310042		U310040	U310043	U310082	U310031

GREASE 182 DS (190kg)

TECHNICAL DATA

-----E310000

PROPERTIES	UNIT	METHOD	VALUE
ACEA	Association Constructeurs Européennes de l'Automobile		
API	American Petroleum institute		
SAE / ISO-VG / NLGI			NLGI 2
COLOUR	Visual		BEIGE
Density @ 15°C	kg / L	ASTM D1298	
Pourpoint	°C	ASTM D97	
Flashpoint COC	°C	ASTM D92	
Cinematic Viscosity @40°C	cSt	ASTM D7279	
Kinematic viscosity @ 100°C	cSt	ASTM D7279	
(V.I.) Viscosity index		ASTM D2270	
Copper Corrosion		ASTM D130	
Anilinepoint	°C	ASTM D611	
Noack evap	% w/w	ASTM D 5800	
DROPPING POINT	°C	ASTMD 2265	190
Sulphated Ash	% weight		
Waterwashtest	% @ 79°C	ISO 11009	< 10
Penetration 60 strokes @ 25°C	1/10mm	ISO 2137	290

For guidelines on emergencies, handling and storage etc., please refer to the SDS/MSDS. This is available on request. Storage of the product: 3 years in a sheltered environment, unopened.

Any handling/disposal/liquidation of the product must comply with local regulations for petrochemicals. Advice will be given on request.