

COMPOUND

CALCIUM GRIP GREASE

310011-310071-310073/08.10

Rev. 0

DESCRIPTION & APPLICATIONS

COMPOUND is particularly suitable for the lubrication of joints and axes:

- Cardan shafts
- Chassis
- Disks and rolling caterpillar drives
- Open gears with low tax
- Chains
- Cam

ADVANTAGES

- Good protection against wear and corrosion.
- Easy pumpable and injectable.
- Hardens not in use.
- Extremely high adhesion power.
- Very good resistance to centrifugal forces.

ENVIRONMENT, HEALTH & SAFETY

Please consult also the Safety Data Sheet about how to manipulate and to stock the product as well as to learn about the first aid measurements in case of accident.

Elimination after use must be made in conformity with the local rules in force about used greases disposal.

When needed, Safety Data Sheet can be obtained upon request.

Conservation of the product: 1 year(s) in closed container and sheltered.

COMPOUND

PROPERTIES

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA	
Color	-	-	Green	Green
Appearance	-	-	Bond	Bond
Thickener	-	-	Calcium	Calcium
Viscosity of the base oil at 40°C	mm²/s (cSt)	NFT 60100	100	100
Viscosity of the base oil at 100°C	mm²/s (cSt)	NFT 60100	7,8	7,8
Dropping point	°C	NFT 60102	95	95
Application temperature	°C	-	-20/+60	-20/+60
Water resistance	-	-	Good	Good
NLGI-grade	-	ASTM D 217	0	1
Penetration at 25°C 60 strokes	1/10 mm	NFT 60132	365	320
Product number	180 K	-	310080	310011
Product number	18 K	-	310073	310071

The average values are given for information only.