

KUTILUB DI AM

NEAT CUTTING FLUID FOR
STEEL AND STAINLESS STEEL

410181/02.24

Rev. 1

DESCRIPTION & APPLICATIONS

DI KUTILUB AM is a neat cutting fluid (not soluble), with excellent cutting characteristics thanks to the synergistic effect between the different additives.

DI KUTILUB AM is designed specifically for cutting operations on steel and alloy steels.

It can also be used for other cutting operations such as turning and milling.

NB: Because of its Additivation EP, this product is not suitable for yellow metals.

-

ADVANTAGES

- Its EP (Extreme Pressure) performance ensuring enhanced tool lifetime.
- Its very good fluidity ensuring excellent cooling and reducing metal losses.
- Multifunctional
- Anti mist properties

ENVIRONMENT, HEALTH & SAFETY

Please consult also the Safety Data Sheet about how to manipulate and to stock the product as well as to learn about the first aid measurements in case of accident.

Elimination after use must be made in conformity with the local rules in force about used oils disposal.

When needed, Safety Data Sheet can be obtained upon request.

Conservation of the product: 3 year(s) in closed container and sheltered.

KUTILUB DI AM

PROPERTIES

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA
Density at 15°C	kg/m ³	NFT 60101	870
Kinematic viscosity at 40°C	mm ² /s (cSt)	NFT 60100	24
Flash point	°C	NFT 60118	181
Color	-	-	amber

The average values are given for information only.