

# SAFELUB DEC HV

Heavy duty product for wire drawing

410263/06.20

Rev. 0

## DESCRIPTION & APPLICATIONS

When a universal product for wire drawing for big, medium and fine thread is required, SAFELUB DEC HV is the first choice. It provides the required lubrication properties for drawing the steel wire as well as the correct cleanliness of the wire for a variety of diameters.

## ADVANTAGES

- High viscosity and stickiness to the wire.
- Extremely high extreme pressure performances in order to reduce the wire at the highest speed.
- Increases the lifetime of moulds, dies and wire rods.
- Very fine surface finishing of the manufactured wire.

## ENVIRONMENT, HEALTH & SAFETY

Please consult also the Safety Data Sheet about how to manipulate and to stock the product as well as to learn about the first aid measurements in case of accident.

Elimination after use must be made in conformity with the local rules in force about used oils disposal. When needed, Safety Data Sheet can be obtained upon request.

Conservation of the product: 3 year(s) in closed container and sheltered.

## PROPERTIES

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA
Density at 15 °C	kg/l	ASTM D4052	0,96
Kinematic viscosity at 40°C	mm <sup>2</sup> /s.	ASTM D445	780
Sulphur content	%	-	3,2
Chlorine content	%	-	<0,01
Color	-	-	Dark brown

*The average values are given for information only.*