

GREASE ULTRA

MULTI-SERVICES EP
GREASE IN SPRAY

500014/08.10

Rev. 0

DESCRIPTION & APPLICATIONS

GREASE ULTRA is ideal for lubricating inaccessible places such as: cables, springs, hinges, guides, etc. ..

GREASE ULTRA is also used to lubricate bearings and joints.

Operating temperature: -20 ° C to 140 ° C, 150 ° C (peak temperature).

ADVANTAGES

- Highly water-resistant, hot or cold water and highly resistant to acids and alkalis.
- Excellent penetrating power. Forms a lubricant film wear resistant and provides long lasting protection against rust and corrosion.

PACKAGING

- Available in white metal sprays of 500 ML.
- Double ball valve for multi-position use.
- Delivered with 2 spray nozzles : 1 short and 1 long (100mm)

ENVIRONMENT, HEALTH & SAFETY

Inflammable ! Do not expose at temperatures above 50°C.

Please consult also the Safety Data Sheet about how to manipulate and to stock the product as well as to learn about the first aid measurements in case of accident.

Elimination after use has to be made in conformity with the local rules in force about used sprays disposal.

Throw away only if completely empty.

Keep out reach of children.

Propulsion gas (propane-butane) with no ozone depletion potential.

Shelf date: 3 years.

GREASE ULTRA

PROPERTIES

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA
Thickener	-	-	Lithium
Color	-	-	yellow/beige
NLGI-grade	-	ASTM D 217	2
Penetration at 25°C 60 strokes	1/10 mm	NFT 60132	265 / 295
Viscosity of the base oil at 40°C	mm ² /s (cSt)	NFT 60100	180
Dropping point	°C	NFT 60102	190
Application temperature	°C	-	-20 / + 140

The average values are given for information only and ...